

Client		Date	
--------	--	------	--

Dimensions (net opening) mm (the measures must be indicated in multiples of 50 mm)	L=	H=
---	----	----

Motorgear position	Lateral on the left	Lateral on the right
for H < 5000 mm, X = 850 mm for H ≥ 5000 mm, X = 1100 mm Counterweight overall dimensions (option)* extra space for installation/maintenance		

Temperature difference between the two environments (°C)	T=
--	----

Frame	Galvanized steel	Painted galvanized steel* RAL
Fixing	Metal structure	Brick wall
Application	Indoor	Outdoor
Safety	Standard: Safety edge + 2 pairs of photocells	Safety edge + Optical barriers - in compliance with the EN 12445 standard* only for dry environments

Control Box position L max of the cable = 9 m		
	Motor gear side	Opposite side of the motor gear
Other positions:		

Porthole				
	1 line	2 lines (standard)	3 lines*	4 lines*

AVAILABLE RAL																
Fabric	900 gr/m²	RAL	1003	1021	2004	3002	6026	5010	5012	9005	7037	9006	7038	7035	1013	9016
Class B-s2,d0 fabric*	900 gr/m² *	RAL	6026	5002	9005	7038	9016									
Customized fabric*																

* available with additional price

ADDITIONAL DEVICES*

Opening devices	 Pulling cable n° assembly kit:	 04071108 Support for rope n°	 03201147 Kit 2 buttons + receiver n°
	 Radar n° assembly kit:	 Crank 1m n°	 Crank 3m n°
	 04530101 Black push button Ø90 (1 std.) + n°	 04110505 Infrared touchless sensor (indoor applications) n°	 04302227 Infrared touchless sensor (industrial applications) n°
	 04110302 Numeric keypad with card reader n°	 03201425 Remote control (2) + Receiver (1) 5 channels n°	 04110313 Remote control 5 channels n°
	 04110314 Receiver for 5 channels transmitter n°	 Remote control (2) + Receiver (1) 128 channels n°	 04110527 Remote control 128 channels n°
	 04110528 Receiver for 128 channels transmitter n°	 03201111 Loop detector – two channels kit L=10 m n°	 04111602 Badge n°
Safety devices	 03201153 24V micro flash yellow flashing n°	 04110305 Single 24V panel flashing yellow with box n°	 04302208 Single 24V panel flashing yellow n°
	 04110304 Double 24V panel flashing yellow n°	 04302180 Traffic light n°	 04302537 24v 220ma siren 65 decibel with flashing light n°
	 Manual counterweight system	 04181586 Stand for UPS housing	 04302583 UPS panel + plug (backup power supply, in case of fault in the power supply)
	 04110282 Relay fo UPS	 02030109 / 02030110 Door protection pole H n°	 Brush
	 Box gasket	 Junction box	 400V 3F / 220V 1F Transforme
	 04071018 Document tray 220x310x55 n°	 04016075 Chain oil 400 ml n°	

Notes

* available with additional price

La riproduzione non autorizzata è vietata per tutti i contenuti di questo documento di proprietà di Incold S.p.A. | Unauthorized reproduction is prohibited for all content of this document as property of Incold S.p.A.