


Client		Date	
--------	--	------	--

Dimensions (net opening) mm - max 3000x3000 (the measures must be indicated in multiples of 50 mm)	L=		H=	
---	----	--	----	--



Temperature difference between the two environments (°C)	T=	
--	----	--

Model	PURA K-IX Frame and cover in 304 stainless steel
-------	--

Safety	Standard safety systems: Optical barriers (only for $L \geq 1000$ mm)
--------	--

Fixing	On panel	Panel thickness (mm):	
	OPTION: Stainless steel edging (to cover the cut on the panels)*		
	Opposite to a sliding door	Panel thickness (mm):	
	On metallic structure		
	On masonry		

Portholes	 1 line*	 2 lines*	 high visibility*	 without portholes
-----------	--	---	---	--

			AVAILABLE RAL														
Fabric	650 gr/m²	White	Fabric adapted for contact with foods														
	900 gr/m²	RAL		1003	1021	2004	3002	6026	5010	5012	9005	7037	9006	7038	7035	1013	9016
Class B-s2,d0 fabric*	900 gr/m² *	RAL		6026	5002	9005	7038	9016									
	Customized fabric*																

Nice side of the fabric	Front (motorgear side)	Opposite side of the motorgear
-------------------------	------------------------	--------------------------------

* available with additional price

La riproduzione non autorizzata è vietata per tutti i contenuti di questo documento di proprietà di Incold S.p.A. | Unauthorized reproduction is prohibited for all content of this document as property of Incold S.p.A.

ADDITIONAL DEVICES*

 Remote control with IRMOS		
Opening devices	 Pulling cable assembly kit: n°	04071108  Support for rope n°
	 Radar assembly kit: n°	04110505  Infrared touchless sensor (indoor applications) (1 std.) + n°
	04530101  Black push button Ø90 n°	04530219  Remote control panel 6 m wires n°
	04110302  Numeric keypad with card reader n°	04110313  Remote control 5 channels n°
	03201425  Remote control (2) + Receiver (1) 5 channels n°	04110527  Remote control 128 channels n°
	 Remote control (2) + Receiver (1) 128 channels n°	03201111  Loop detector – two channels kit L=10 m
		03201147  Kit 2 buttons + receiver n°
		04302227  Infrared touchless sensor (industrial applications) n°
		 kit for interlocking door system (IRMOS required on both doors)
		04110314  Receiver for 5 channels transmitter n°
		04110528  Receiver for 128 channels transmitter n°
		04111602  Badge n°

Safety devices	03201153  24V micro flash yellow flashing n°	04110305  Single 24V panel flashing yellow with box n°
	04110304  Double 24V panel flashing yellow n°	04302180  Traffic light n°
	04181586  Stand for UPS housing	04302583  UPS panel + plug (backup power supply, in case of fault in the power supply)
	02030109 / 02030110  Door protection pole H n°	04302208  Single 24V panel flashing yellow n°
		04302537  24v 220ma siren 65 decibel with flashing light n°
		04110282  Relay for UPS

 Box gasket (std insulated fabrics)	 Junction box	 400V 3F / 220V 1F Transforme
04071018  Document tray 220x310x55 n°		

Notes

* available with additional price

La riproduzione non autorizzata è vietata per tutti i contenuti di questo documento di proprietà di Incold S.p.A. | Unauthorized reproduction is prohibited for all content of this document as property of Incold S.p.A.